

GAIT 5

Specifications

Year Built	2010
Max. Pulling Capacity (lbs)	460,000 lbs.
Max. Snubbing Capacity (lbs)	225,000 lbs.
Stroke (ft)	10'
BOP	13-5/8", 5000 psi
Power Slip	400,000 lbs.
Rotary Torque & Speed	22,000 ft/lbs & 60RPM
Through Bore	14"
Tubular Handling	1.66" – 9 5/8"
Gin Pole Lift (SWL)	10MT, 62FT
Wind Speed	65 knots
Ladder Type	Zig Zag
Skidding Feature	X-Y Skidding System
Pipe Racking System	None



GAIT 6

Specifications

Year Built	2014
Max. Pulling Capacity (lbs)	460,000 lbs.
Max. Snubbing Capacity (lbs)	225,000 lbs.
Stroke (ft)	10'
BOP	13-5/8", 5000 psi
Power Slip	400,000 lbs.
Rotary Torque & Speed	22,000 ft/lbs & 60RPM
Through Bore	14"
Tubular Handling	1.66" – 9 5/8"
Gin Pole Lift (SWL)	10MT, 72FT
Wind Speed	65 knots
Ladder Type	Zig Zag & Caged Ladder
Skidding Feature	X-Y Skidding System
Pipe Racking System	192 Stands of Double Pipe racking (Max 4" DP)